

# Material Safety Data Sheet

## PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Country Chic Paint - furniture & home decor paint

HMIS Codes: H-1 F-0 R-0 P-C

**Product Description:** Chalk and mineral-based furniture & home decor paint

**Supplier Details:** Country Chic Paint Ltd., #4-5 - 2994 Boys Road, Duncan BC V9L 6W4, Canada

**Telephone:** 1-888-523-2360 (8:00 am - 4:30 pm PST)

## HAZARDS IDENTIFICATION AND COMPOSITION

| Reportable Components | CAS Number | Weight Percent |
|-----------------------|------------|----------------|
| * Titanium Dioxide    | 13463-67-7 | 5-30           |

PEL (OSHA) : 15 mg/m<sup>3</sup>, TOTAL DUST, 8 HR TWA - TLV (ACGIH): 10 mg/m<sup>3</sup>, TOTAL DUST, 8 HR TWA

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. This product is believed not to contain materials listed in Section 112(b) of the Clean Air Act.

## FIRST AID MEASURES

**SKIN:** Wash exposed area with soap and water.

**EYES:** Flush with large amounts of water.

**INGESTION:** Drink a glass of water to dilute. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomit. Rinse mouth, administer more water. Contact a physician immediately.

**INHALATION OVEREXPOSURE:** Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention.

## FIRE FIGHTING MEASURES

**Flash Point:** Not Applicable

**Method Used:** Not Applicable

**Extinguishing Media:** Use extinguishing media appropriate to surrounding fire

**Firefighting Procedures:** For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode to protect against the hazardous effects of normal products of combustion or oxygen deficiency.

**Unusual Fire and Explosion Hazards:** Product may spatter if temperature of liquid exceeds the boiling point of water. If solids ignite, toxic and irritating gases can be emitted. Thermal decomposition of this product will produce carbon monoxide and carbon dioxide gases.

## ACCIDENTAL RELEASE MEASURES

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Prevent run-off sewers, streams, or other bodies of water.

## HANDLING AND STORAGE

Store in a cool, dry area. Keep from freezing. Keep away from heat sources. Clean rim of container after each use and keep containers closed when not in use. Use only with adequate ventilation.

**Other Precautions:** Containers of this material may be hazardous when emptied. Since emptied containers may retain product residues (vapor, liquid, and/or solid), all precautions given in this data sheet must be observed.

## EXPOSURE CONTROLS / PERSONAL PROTECTION

**Respiratory Protection:** Not normally required when applying by brush or roller. When spraying, wear a mist/dust particulate respirator. In cases of poor or no ventilation, wear a respirator NIOSH approved for organic vapours and particulates.

**Ventilation:** General (dilution) ventilation is required during use. Local exhaust ventilation is required during operations where this material is heated.

**Protective Gloves:** Wear resistant gloves such as: BUNA-N

**Eye Protection:** Chemical splash goggles in compliance with OSHA regulations are advised, when risk of splattering exists, unless full facepiece respirator is worn.

**Other Protective Clothing or Equipment:** Use impermeable aprons and protective clothing to prevent skin contact.

**Work / Hygienic Practices:** Wash hands with soap and water after handling this product.

## PHYSICAL AND CHEMICAL PROPERTIES

**Coating Volatile Organic Compounds (VOC):** 0 grams / liter

**Material Volatile Organic Compounds (VOC):** 0 grams / liter

**Boiling Range:** Not Applicable

**Specific Gravity (H<sub>2</sub>O=1):** 1.29-1.39

**Vapor Density:** Heavier than air

**Evaporation Rate:** Slower than Butyl Acetate

**Physical State:** Liquid

**Solubility in Water:** Soluble

**Appearance and Odor:** moderately thick liquid with low odor

**Freezing Point:** 0 °C / 32 °F

## STABILITY AND REACTIVITY

**Stability:** Stable                    **Hazardous Polymerization:** Will not occur

**Conditions to Avoid:** Excessive temperatures, poor ventilation, and corrosive atmospheres. Avoid all heat sparks and sources of ignition.

**Incompatibility (Materials to Avoid):** Strong oxidizing agents

**Hazardous Decomposition or Byproducts:** Normal combustion forms carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

## TOXICOLOGICAL INFORMATION

**Health Hazards (Acute and Chronic):** Not considered a carcinogen by IARC, NTP or OSHA. No chronic health hazards.

**Health Hazards of Previous Coatings:**

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. For additional information, Canadian customers contact the Product Safety division of Health Canada at 1-800-0-CANADA. US customers contact the U.S. EPA/Lead Information Hot Line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

**Carcinogenicity:** NTP   **Carcinogen:** No   **IARC Monographs:** Yes   **OSHA REGULATED:** No

This material is not listed as a human carcinogenic.

**Inhalation Health Risks And Symptoms Of Exposure:** Use only with adequate ventilation. If adequate ventilation is not possible, such as in a closed room or other situations where air flow is minimal or nonexistent, see section titled "EXPOSURE CONTROLS / PERSONAL PROTECTION" for information regarding respiratory protection. Do not breathe dust or spray mist. Ensure fresh air entry during application and drying. For spray application, sanding, abrading, and dust cleanup, wear an appropriate and properly fitted respirator (NIOSH/MSHA TC21C approved). Follow respirator manufacturer's directions for respirator use. If affected, remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Get medical attention.

**Skin And Eye Contact Health Risks And Symptoms Of Exposure:** Exposure may cause drying of the skin with mild irritation. Symptoms may include: redness, burning sensation, drying and cracking. Exposure with material may cause moderate eye irritation. Symptoms may include: tearing, redness, and stinging sensation. Corneal involvement or visual impairment is not expected to occur.

**Skin Absorption Health Risks And Symptoms Of Exposure:** May dry and defat skin causing cracks, irritation and dermatitis.

**Ingestion Health Risks and Symptoms of Exposure:** Excessive breathing of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and asphyxiation. Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into lungs and cause chemical pneumonitis which can be fatal. No effects known in ordinary use of product.

**Medical Conditions Generally Aggravated by Exposure:** None known.

## **DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Destroy by liquid incineration. Material collected on absorbent material may be deposited in an approved landfill in accordance with local, state, and federal regulations.

## **TRANSPORT INFORMATION**

Product should be kept from freezing during transportation and appropriate protective packaging should be used to avoid leaks.

## **REGULATORY INFORMATION**

This MSDS has been prepared to meet the requirements of the CPR and contains all of the information required.

## **OTHER INFORMATION**

This information provided as a resource only. It should not be taken as a warranty or representation for which Country Chic Paint Ltd. assumes legal responsibility. The information contained herein is believed to be accurate and obtained from sources believed to be reliable. It is the responsibility of the user to investigate and verify its validity. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state, and local regulations. Country Chic Paint Ltd. will not be held liable for claims relating to use of this information or recommendations.

**Date:** October 19, 2016

**Prepared by:** Country Chic Paint Ltd. - 1-888-523-2360